


FEATURES AND BENEFITS


- Lightweight and produces a finely atomized, intermittent liquid spray using only the liquid pressure as the force for atomization.
- Internal air cylinder automatically interrupts the liquid flow at any desired frequency up to 180 cycles per minute.
- Minimum air pressure of 75 psi (5 bar) is required for the air cylinder.
- The nozzle operates at liquid pressures up to 4000 psi (280 bar).
- **Key feature overview for 24AUA:**
 - 1/2" (12.7 mm) diameter mounting hole and locking screw for quick installation and easy positioning on a mounting bar.
 - Shut-off needle and valve seat are available in tungsten carbide or stainless steel.
 - Valve seat is located directly behind the spray tip for drip-free shut-off.
 - Rear knob locks the shut-off needle in place to prevent accidental discharge while changing spray tips.
 - The liquid inlet connection is available in the standard "down" position or one of seven other positions in intervals of 45°.
- **Key feature overview for 24AUA-20190:**
 - Same as 24AUA but has an aluminum support body and end cap which reduce the nozzle's total weight to just 1-1/4 lbs. (0.6 kg).
 - Operates at liquid pressures up to 3000 psi (210 bar) and requires a minimum air pressure of 42 psi (3 bar) for the air cylinder.
- **Key feature overview for 24AUA-8395:**
 - Same as 24AUA but with two liquid inlets that allow continuous recirculation of the sprayed liquid between the nozzle and the liquid supply.
- **Key feature overview for 24AUA-8980:**
 - Same as 24AUA but equipped with an extension in a choice of lengths.
 - Valve stem extends throughout the length of the extension and the valve seat is directly behind the spray tip for instantaneous, drip-free control.

24AUA




Maximum fluid pressure:
4000 psi (280 bar)
Capacity: 0.6 gpm (2.3 l/min)

24AUA-20190



Maximum fluid pressure:
3000 psi (210 bar)
Capacity: 0.6 gpm (2.3 l/min)

24AUA-8395



Maximum fluid pressure:
4000 psi (280 bar)
Capacity: 0.6 gpm (2.3 l/min)

24AUA-8980



Maximum fluid pressure:
4000 psi (280 bar)
Capacity: 0.6 gpm (2.3 l/min)

