



FEATURES AND BENEFITS

- Solid cone-shaped spray pattern with round impact area.
- Uniform distribution over a wide range of flow rates and pressures.
- Medium- to large-sized drops.
- Unique vane design with large flow passages provides superior control and uniform distribution.
- Removable caps and vanes for easy inspection and cleaning on most models.
- Removable vane has location marks for proper positioning after cleaning.
- Set screws in some models secure the vane in the nozzle to prevent dislocation caused by vibration.
- Polypropylene material option offers exceptional chemical and corrosion resistance and resists caking and buildup.
- Wall-mounted options for installation on room exterior, vessel or pipeline.
- For installations with space limitations, right-angle mounting options allow for mounting at a 90° angle.

G



Removable cap and vane
1/8" to 1/2" NPT or BSPT (F)

GG



Removable cap and vane
1/8" to 1/2" NPT or BSPT (M)

H



One-piece body
3/4" to 1" NPT or BSPT (F)

H



Removable vane/cast body
1-1/4" to 8" NPT or BSPT (F)

H



Removable vane/Polypropylene
1-1/2" to 2" NPT or BSPT (F)
Maximum temperature rating is
150°F (66°C)

HF



Removable vane/cast body
4" to 10" flange connection

HH



One-piece body
1/8" to 1" NPT or BSPT (M)

GD



Wall-mounted
Removable cap and vane
1/8" to 1/2" NPT or BSPT (F)

