



K



1/8" to 1" NPT or BSPT (M)

FEATURES AND BENEFITS

- Wide-angle flat fan spray pattern with uniform distribution and medium impact.
- Medium-sized drops.
- Unobstructed flow passages minimize clogging.
- Precision engineered for dependable, accurate control of deflection and spray angle.

OPTIMIZATION TIPS

- See page C2 for optimization tips.

APPLICATIONS

- Cooling conveyor belts
- Film washing
- Fire suppression/prevention
- Foam knockdown
- Spray agitation
- Spraying eliminator plates
- Water curtain

SEE ALSO



- Accessories
 - Adjustable ball fittings
 - Check valves
 - Jet stabilizers for reduced turbulence
 - Pressure gauges
- Pressure relief valves
- Split-eyelet connectors
- Strainers
- Swivel connectors

DIMENSIONS AND WEIGHTS

Standard	Nozzle Type	Orifice Dia. Nom. (in.)	Length (mm)	Hex. (mm)	Net Weight (kg)
	K (M)	1/8	25.4	11.1	.015
		1/4	30.9	14.3	.03
		3/8	44.5	17.5	.06
		1/2	51	22.2	.11
		3/4	65.1	38.1	.40
		1	92.1	47.6	.91

Based on largest/heaviest version of each type.

MATERIALS

Material	Material Code	Nozzle Type
		K
Brass	(none)	●
303 Stainless Steel	SS	●
316 Stainless Steel	316SS	●
Polyvinyl Chloride	PVC	●

Other materials available upon request.

ORDERING INFO

STANDARD SPRAY NOZZLE			
1/8	K	- SS	2
Inlet Conn.	Nozzle Type	Material Code	Capacity Size

BSPT connections require the addition of a "B" prior to the inlet connection.

