

# RotoClean® Airless Spray Nozzles

## Benefits

- Ideal for high-pressure manual paint spraying with Spraying Systems Co. and other manufacturers' airless spray guns
- Quick and easy to unclog. Simply rotate tip 180° and blow obstructions out of the opening in the back of the tip
- Tungsten carbide orifice provides maximum erosion resistance for high-pressure spraying
- Easy to replace the orifice – no need to disassemble
- Guard safety feature

## Specifications

Maximum pressure: 5000 psi (345 bar)

Spray pattern: Flat spray

Materials: Stainless steel holder with tungsten carbide orifice insert and protective nylon lugs



106A RotoClean

225 RotoClean

## Compatible Spray Guns

RotoClean No.		Connection Thread Size	Gasket No.	For
106A-2	225-2	11/16"-16	7894-NY	SPRAYING SYSTEMS CO. 24 AUA AND GRACO
*106A-3	225-3	3/4"-16	19078-NY	BALCRANK
106A-6	225-6	7/8"-14	11918-NY	GRACO
106A-8	225-8	3/8" NPS	12552-NY	NORDSON
106A-9	225-9	3/8" NPS	10660-NY	DEVILBISS
**106A-10	225-10	3/4"-20	19079-NY	BINKS 50
106A-11	225-11	M18 x 1 Metric	7894-NY	ATLAS COPCO
106A-12	225-12	3/8" NPS	7894-NY	SPEE-FLO
106A-13	225-13	M18 x 1 Metric	7894-NY	DEICKE & KOPPERSCHMIDT
106A-14	225-14	1-14	9632-NY	SPRAYING SYSTEMS CO. 44 AUA
106A-15	225-15	11/16"-16	12552-NY	BINKS 43
106A-16	225-16	5/8"-14 BSPP	11918-NY	—
106A-17	225-17	11/16"-16	13358-NY	WAGNER
106A-18	225-18	M18 x 1.5 Metric	7894-NY	—

\* Use Gasket No. 7894-NY for 106A-3.

\*\* Use Gasket No. 12552-NY for 106A-10.