

PathoSans® On-Site Generation Technology System Overview



PathoSans on-site generation systems are available in a variety of sizes to meet different volume requirements and ensure you always have the needed amount of cleaner and disinfectant readily available. Functionally, the systems are the same. The size of the individual components varies, but every system produces two, highly effective, non-toxic solutions using just salt, water and electricity:

- PathoClean® sodium hydroxide cleaner/degreaser
- PathoCide® hypochlorous acid disinfectant/sanitizer

PathoSans CTC Key System Components:



REQUIRED FOR OPERATION

- 110 VAC (15A) – GFCI outlet
- 0.75" diameter floor-level drain
- Domestic cold water input; 50-90°F (10-32°C) and 35-80 psi (2.5-5.5 bar)
- 99.9% approved NaCl salt
- 18" (46 cm) of head clearance for salt fill and cell replacement
- Adequate cellular network coverage for remote communication

PATHOSANS • THE CLEAN THAT SAYS YOU CARE



PS600-CT



PS600-CT 25 GALLON



PS600-CTC

CONCENTRATE SYSTEM DIMENSIONS

System		Height In. (Cm)	Width In. (Cm)	Depth In. (Cm)
PS600-CT		75 (190.5)	29 (73.7)	32 (81.3)
PS600-CT 25 Gallon		78 (198.1)	57 (144.8)	27 (68.6)
CTC System with Water Softener Dimensions	Transport Tanks Add-on	65 (165.1)	46 (116.8)	19 (48.3)
	Dilution Station Add-on	65 (165.1)	52 (132.1)	19 (48.3)
CTC System with Cartridge Water Softener	Transport Tanks Add-on	65 (165.1)	31 (78.7)	23 (58.4)
	Dilution Station Add-on	65 (165.1)	38 (96.5)	16 (40.6)



PS600-40



PS600-80



PS6020

READY-TO-USE SYSTEM DIMENSIONS

System	Height In. (Cm)	Width In. (Cm)	Depth In. (Cm)
PS600-40	75 (190.5)	25 (63.5)	28 (71.1)
PS600-80	82 (208.3)	32 (81.3)	30 (76.2)
PS6020	79 (200.6)	30.25 (76.8)*	30.25 (76.8)*

*System only. Does not include tanks.

1.833.553.2648 PathoSans.com

100 W. Lake Dr., Glendale Heights, IL 60139